

# Semiautomatiche

Semiautomatic - Semi-automatique



EASY 400PT



EASY 460PT

## Capacità di taglio - Cutting capacity - Capacité de coupe

### EASY 400PT

|   |    | 0°      | 45°     | 60°     | -45°    | -60°    |
|---|----|---------|---------|---------|---------|---------|
| ● | mm | 150     | 150     | 150     | 150     | 150     |
| ○ | mm | 400     | 400     | 280     | 400     | 260     |
| □ | mm | 400     | 380     | 280     | 380     | 260     |
| ▭ | mm | 400x550 | 300x420 | 400x280 | 300x410 | 400x230 |

### EASY 460PT

|   |    | 0°      | 45°     | 60°     | -45°    | -60°    |
|---|----|---------|---------|---------|---------|---------|
| ● | mm | 200     | 200     | 200     | 200     | 200     |
| ○ | mm | 460     | 450     | 300     | 450     | 240     |
| □ | mm | 450     | 410     | 300     | 430     | 300     |
| ▭ | mm | 450x620 | 450x340 | 420x270 | 450x400 | 320x220 |

## Caratteristiche tecniche - Technical features - Caractéristiques techniques

|                         |                    |                          |      | EASY 400PT     | EASY 460PT     |
|-------------------------|--------------------|--------------------------|------|----------------|----------------|
| Misure lama             | Blade dimension    | Dimension de la lame     | mm   | 4610x34x1,1    | 5270x34x1,1    |
| Velocità rotazione lama | Blade speed        | Vitesse de coupe         | m/1' | 20/63          | 23/95          |
| Motore rotazione lama   | Blade motor power  | Moteur du ruban          | Kw   | 2,2            | 2,2            |
| Peso approssimativo     | Weight (approx.)   | Poids (approx.)          | Kg   | 820            | 1250           |
| Dimensioni d'ingombro   | Overall dimensions | Dimensions de la machine | mm   | 2830X1725X2275 | 3050X1890X2500 |