

36015 SCHIO (VI) ITALY - VIA LAGO DI ALLEGHE (Z.I.) - TEL. 0445/576129

FAX. 0445/575910 - http://www.simecsrl.it - E-mail: simec@simecsrl.it

SIMAX 100

Indicative Production per Hour (100 % of capacity) with TCT blade and bars of 6000 mm length.

material: Steel 18NiCrMo5
Cutting speed: 120 m/min
Blade diameter: Ø360 mm

N° of teeth: Z 80

Removal for teeth: 0.07mmBlade thickness: 2.26 mmPieces length: 100mm

Bar diameter	Cutting time	Downtime	Cycle time (s)	Pieces/hour
Ø (mm)	(s)	(s)		
32	4.5	3	7.5	480
40	5.3	3	8.3	435
55	6.9	3	9.9	365
65	7.8	3	10.8	335
70	8.3	3	11.4	316
80	9.4	3	12.4	290
90	10.4	3	13.4	268
100	11.4	3	14	258

NOTE

The cycle time, is the sum of **cutting time** and **downtime** (head movement back + opening and closing vice + feeding considering even the change bar and trim cut).

Supposing to cut pieces 80÷100mm long, the downtime will be 3 second.

BLADE LIFE

The best TCT blade has a life (measured in square meters) that varies between 50 and 80 m².

50 m² corresponds to 61.500 pieces Ø 32

to 40.000 pieces Ø 40 to 22.500 pieces Ø 55 to 15.200 pieces Ø 65 to 13.000 pieces Ø 70 to 10.000 pieces Ø 80 to 8.000 pieces Ø 90 to 6.300 pieces Ø 100